

Sealed VFDs for compact industrial machines

Reduce cabinets, cabling and commissioning work with a drive configured for your machine.

230 V 1-phase input | 230 V 3-phase motor output



IP64 HOUSING

Power range positioned for OEM machinery

CORE OEM MODEL

2.2 kW

our main serial product

CONFIGURED OPTIONS

0.75 / 1.5 kW

for lower-power machines

PROJECT OPTION

up to 3 kW*

confirmed per application

Built to simplify your machine

- Compact installation**
One module close to the machine instead of a standard VFD in a separate cabinet.
- OEM configuration**
Parameters, controls and operating range prepared for the application.
- Direct manufacturer support**
Fast technical feedback, customisation and private-label options.

Technical essentials

PROTECTION	Documented IP64 enclosure
CONTROL	Local panel and external 0-10 V input
FREQUENCY	Configurable output from 1 to 1000 Hz
SIGNALS	Run and fault outputs
SAFEGUARDS	Short-circuit, overload and thermal

PROVEN IN SERIAL PRODUCTION

Multi-year OEM use by a European belt-grinder manufacturer

A field-proven application in metal-dust environments - customer identity kept confidential.

Let's compare your current VFD setup

15-minute technical review | 1-2 sample units | OEM configuration

Jan Scislowicz

+48 573 935 143

emfal@emfal.pl

www.sealedinverter.pl

* The 3 kW variant is a project option; final enclosure, IP and EMC scope is confirmed for each application. System-level EMC compliance depends on the agreed installation configuration, including required filtering and input choke.

Product overview for initial OEM discussion. Final parameters are confirmed in the application-specific datasheet and offer.